



1		2		3		4																																																								
A	Technical sheet / Datos técnicos:							A																																																						
B	Part number adaptable to / Referencia adaptable a					4613192500		B																																																						
	Operating pressure / Presión de trabajo					max. 10 bar																																																								
	Predominance / Predominancia					≤ 0,4 bar																																																								
	Permissible medium / Medio de funcionamiento					Air / Aire																																																								
	Operating temperature range / Rango de temperatura					-40°C to / a +80°C																																																								
Weight / Peso					1400 gr		C																																																							
D	 							D																																																						
E	<table border="1"> <thead> <tr> <th>Port / Conexión</th> <th>Function / Función</th> <th>Thread / Rosca</th> </tr> </thead> <tbody> <tr> <td>11</td> <td>Supply / Alimentación</td> <td>M22x1,5 VOSS</td> </tr> <tr> <td>12</td> <td>Supply / Alimentación</td> <td>M22x1,5 VOSS</td> </tr> <tr> <td>4</td> <td>Control / Pilotaje</td> <td>M16x1,5 VOSS</td> </tr> <tr> <td>21</td> <td>Delivery / Salida</td> <td>M22x1,5 VOSS</td> </tr> <tr> <td>22</td> <td>Delivery / Salida</td> <td>M22x1,5 VOSS</td> </tr> <tr> <td>3</td> <td>Exhaust / Escape</td> <td>Tube / Tubo 90°</td> </tr> </tbody> </table>							Port / Conexión	Function / Función	Thread / Rosca	11	Supply / Alimentación	M22x1,5 VOSS	12	Supply / Alimentación	M22x1,5 VOSS	4	Control / Pilotaje	M16x1,5 VOSS	21	Delivery / Salida	M22x1,5 VOSS	22	Delivery / Salida	M22x1,5 VOSS	3	Exhaust / Escape	Tube / Tubo 90°	E																																	
	Port / Conexión	Function / Función	Thread / Rosca																																																											
	11	Supply / Alimentación	M22x1,5 VOSS																																																											
	12	Supply / Alimentación	M22x1,5 VOSS																																																											
	4	Control / Pilotaje	M16x1,5 VOSS																																																											
	21	Delivery / Salida	M22x1,5 VOSS																																																											
	22	Delivery / Salida	M22x1,5 VOSS																																																											
3	Exhaust / Escape	Tube / Tubo 90°																																																												
F	Purpose / Propósito: Application of service brake system through the pedal actuation by the driver. / Aplicación del freno de servicio mediante la actuación del pedal por parte del conductor.							F																																																						
	Installation requirements / Requisitos para la instalación: The design of the foot brake valve, acting on seat, must guarantee the maximum way of the push rod that is necessary to control the valve even in case of failure in the circuit I. Mounting is accomplished with four M8 mounting bolts. / El diseño de la válvula de freno de pie, accionándolo desde el asiento, debe garantizar el máximo recorrido de la varilla de empuje que resulta necesario para el accionamiento de la válvula, incluso en caso de que falle el circuito I. El montaje se efectúa con cuatro pernos de montaje M8.																																																													
<table border="1"> <thead> <tr> <th rowspan="2">Modification nº</th> <th rowspan="2">Modified</th> <th rowspan="2">Date</th> <th rowspan="2">Reason</th> <th rowspan="2">General Tolerance</th> <th colspan="2">Assembly</th> </tr> <tr> <th>Part name</th> <th>ID. Reference</th> </tr> </thead> <tbody> <tr> <td>4</td> <td></td> <td></td> <td></td> <td></td> <td>Drawn</td> <td rowspan="4">  </td> </tr> <tr> <td>3</td> <td></td> <td></td> <td></td> <td></td> <td>03/12/14 L.S.</td> </tr> <tr> <td>2</td> <td></td> <td></td> <td></td> <td></td> <td>Checked</td> </tr> <tr> <td>1</td> <td></td> <td></td> <td></td> <td></td> <td>03/12/14 A.L.</td> </tr> <tr> <td colspan="5">Comments</td> <td>-</td> <td>Part name</td> <td>Foot brake valve</td> </tr> <tr> <td colspan="5" rowspan="3"></td> <td>Material</td> <td>ID. Reference</td> <td>2212511</td> </tr> <tr> <td>-</td> <td>Scale: -</td> <td rowspan="2">  </td> <td rowspan="2">Sheet 1/2</td> </tr> <tr> <td>-</td> <td>Review: 0</td> </tr> </tbody> </table>							Modification nº	Modified	Date	Reason	General Tolerance	Assembly		Part name	ID. Reference	4					Drawn		3					03/12/14 L.S.	2					Checked	1					03/12/14 A.L.	Comments					-	Part name	Foot brake valve						Material	ID. Reference	2212511	-	Scale: -		Sheet 1/2	-	Review: 0
Modification nº	Modified	Date	Reason	General Tolerance	Assembly																																																									
					Part name	ID. Reference																																																								
4					Drawn																																																									
3					03/12/14 L.S.																																																									
2					Checked																																																									
1					03/12/14 A.L.																																																									
Comments					-	Part name	Foot brake valve																																																							
					Material	ID. Reference	2212511																																																							
					-	Scale: -		Sheet 1/2																																																						
					-	Review: 0																																																								
PG/18/02 rev.1 1																																																														
2		3		4																																																										

