





1		2		3		4	
A							
Technical sheet / Datos técnicos:							
Part number adaptable to / Referencia adaptable a						4613154650	
Operating pressure / Presión de trabajo						max. 10 bar	
Predominance / Predominancia						≤ 0,2 bar	
Permissible medium / Medio de funcionamiento						Air / Aire	
Operating temperature range / Rango de temperatura						-40°C to / a +80°C	
Weight / Peso						1100 gr	
B							
							
C							
Port / Conexión		Function / Función			Thread / Rosca		
11		Supply / Alimentación			M16x1,5 & M12x1,5		
12		Supply / Alimentación			M16x1,5 & M12x1,5		
21		Delivery / Salida			M16x1,5		
22		Delivery / Salida			M16x1,5		
3		Exhaust / Escape			Tube / Tubo 90°		
D							
Purpose / Propósito:							
Application of service brake system through the pedal actuation by the driver. / Aplicación del freno de servicio mediante la actuación del pedal por parte del conductor.							
E							
Installation requirements / Requisitos para la instalación:							
The design of the foot brake valve, acting on seat, must guarantee the maximum way of the push rod that is necessary to control the valve even in case of failure in the circuit I. Mounting is accomplished using four screws M8. / El diseño de la válvula de freno de pie, accionándolo desde el asiento, debe garantizar el máximo recorrido de la varilla de empuje que resulta necesario para el accionamiento de la válvula, incluso en caso de que falle el circuito I. El montaje se efectúa mediante cuatro tornillos M8.							
F							
Modification	4					Drawn	
	3					24/11/15 A.U.	
	2					Checked	
	1					24/11/15 A.L.	
	nº	Modified	Date	Reason	General Tolerance	Assembly	
Comments					-	Part name	Foot brake valve
					Material	ID. Reference	2212263
					-	Scale: -	
					-	Review: 0	
Sheet 1/2							
PG/18/02 rev.1 1		2		3		4	

