

1		2		3		4																																																			
Technical sheet / Datos técnicos:																																																									
A	Part number adaptable to / Referencia adaptable a					4613240180																																																			
	Operating pressure / Presión de trabajo					max. 10 bar																																																			
	Predominance / Predominancia					≤ 0,2 bar																																																			
	Permissible medium / Medio de funcionamiento					Air / Aire																																																			
	Operating temperature range / Rango de temperatura					-40°C to / a +80°C																																																			
	Weight / Peso					3950 gr																																																			
B																																																									
C	<table border="1"> <thead> <tr> <th>Port / Conexión</th> <th>Function / Función</th> <th>Thread / Rosca</th> </tr> </thead> <tbody> <tr> <td>11</td> <td>Supply / Alimentación</td> <td>M16x1,5</td> </tr> <tr> <td>12</td> <td>Supply / Alimentación</td> <td>M16x1,5</td> </tr> <tr> <td>13</td> <td>Supply / Alimentación</td> <td>M12x1,5</td> </tr> <tr> <td>21</td> <td>Delivery / Salida</td> <td>M16x1,5</td> </tr> <tr> <td>22</td> <td>Delivery / Salida</td> <td>M16x1,5</td> </tr> <tr> <td>23</td> <td>Delivery / Salida</td> <td>M12x1,5</td> </tr> <tr> <td>3</td> <td>Exhaust / Escape</td> <td>-</td> </tr> </tbody> </table>							Port / Conexión	Function / Función	Thread / Rosca	11	Supply / Alimentación	M16x1,5	12	Supply / Alimentación	M16x1,5	13	Supply / Alimentación	M12x1,5	21	Delivery / Salida	M16x1,5	22	Delivery / Salida	M16x1,5	23	Delivery / Salida	M12x1,5	3	Exhaust / Escape	-																										
	Port / Conexión	Function / Función	Thread / Rosca																																																						
	11	Supply / Alimentación	M16x1,5																																																						
	12	Supply / Alimentación	M16x1,5																																																						
	13	Supply / Alimentación	M12x1,5																																																						
	21	Delivery / Salida	M16x1,5																																																						
	22	Delivery / Salida	M16x1,5																																																						
	23	Delivery / Salida	M12x1,5																																																						
3	Exhaust / Escape	-																																																							
D	Purpose / Propósito: Application of service brake system through the pedal actuation by the driver. / Aplicación del freno de servicio mediante la actuación del pedal por parte del conductor.																																																								
	Installation requirements / Requisitos para la instalación: The design of the foot brake valve, acting on seat, must guarantee the maximum way of the push rod that is necessary to control the valve even in case of failure in the circuit I. Mounting is accomplished with three holes Ø9,5 mm. / El diseño de la válvula de freno de pie, accionándolo desde el asiento, debe garantizar el máximo recorrido de la varilla de empuje que resulta necesario para el accionamiento de la válvula, incluso en caso de que falle el circuito I. El montaje se efectúa por medio de los tres agujeros Ø9,5 mm.																																																								
E	<table border="1"> <tr> <td rowspan="4">Modification</td> <td>4</td> <td></td> <td></td> <td></td> <td>Drawn</td> <td rowspan="4"> </td> </tr> <tr> <td>3</td> <td></td> <td></td> <td></td> <td>30/06/17 J.S.</td> </tr> <tr> <td>2</td> <td></td> <td></td> <td></td> <td>Checked</td> </tr> <tr> <td>1</td> <td></td> <td></td> <td></td> <td>30/06/17 O.V.</td> </tr> <tr> <td rowspan="3">F</td> <td>nº</td> <td>Modified</td> <td>Date</td> <td>Reason</td> <td>General Tolerance</td> <td>Assembly</td> <td>-</td> </tr> <tr> <td colspan="4" rowspan="2">Comments</td> <td>-</td> <td>Part name</td> <td>Foot brake valve</td> </tr> <tr> <td>Material</td> <td>ID. Reference</td> <td>2212603</td> </tr> <tr> <td colspan="4" rowspan="2"></td> <td>-</td> <td>Scale: -</td> <td rowspan="2"> </td> <td rowspan="2">Sheet 1/2</td> </tr> <tr> <td>-</td> <td>Review: 0</td> </tr> </table>							Modification	4				Drawn		3				30/06/17 J.S.	2				Checked	1				30/06/17 O.V.	F	nº	Modified	Date	Reason	General Tolerance	Assembly	-	Comments				-	Part name	Foot brake valve	Material	ID. Reference	2212603					-	Scale: -		Sheet 1/2	-	Review: 0
	Modification	4				Drawn																																																			
		3				30/06/17 J.S.																																																			
		2				Checked																																																			
		1				30/06/17 O.V.																																																			
	F	nº	Modified	Date	Reason	General Tolerance	Assembly	-																																																	
Comments				-	Part name	Foot brake valve																																																			
				Material	ID. Reference	2212603																																																			
				-	Scale: -		Sheet 1/2																																																		
				-	Review: 0																																																				
PG/18/02 rev.1 1		2		3		4																																																			

