



1		2		3		4																																																																													
A																																																																																			
Technical sheet / Datos técnicos:																																																																																			
Part number adaptable to / Referencia adaptable a						MB4811																																																																													
Operating pressure / Presión de trabajo						max. 10,5 bar																																																																													
Predominance / Predominancia						≤ 0,5 bar																																																																													
Permissible medium / Medio de funcionamiento						Air / Aire																																																																													
Operating temperature range / Rango de temperatura						-40°C to / a +80°C																																																																													
Weight / Peso						1700 gr																																																																													
B																																																																																			
C																																																																																			
<table><tr><th>Port / Conexión</th><th>Function / Función</th><th>Thread / Rosca</th></tr><tr><td>11</td><td>Supply / Alimentación</td><td>M22x1,5 VOSS</td></tr><tr><td>12</td><td>Supply / Alimentación</td><td>M22x1,5 VOSS</td></tr><tr><td>4</td><td>Control / Pilotaje</td><td>M16x1,5 VOSS</td></tr><tr><td>21</td><td>Delivery / Salida</td><td>M22x1,5 VOSS</td></tr><tr><td>22</td><td>Delivery / Salida</td><td>M22x1,5 VOSS</td></tr><tr><td>3</td><td>Exhaust / Escape</td><td>M22x1,5</td></tr></table>								Port / Conexión	Function / Función	Thread / Rosca	11	Supply / Alimentación	M22x1,5 VOSS	12	Supply / Alimentación	M22x1,5 VOSS	4	Control / Pilotaje	M16x1,5 VOSS	21	Delivery / Salida	M22x1,5 VOSS	22	Delivery / Salida	M22x1,5 VOSS	3	Exhaust / Escape	M22x1,5																																																							
Port / Conexión	Function / Función	Thread / Rosca																																																																																	
11	Supply / Alimentación	M22x1,5 VOSS																																																																																	
12	Supply / Alimentación	M22x1,5 VOSS																																																																																	
4	Control / Pilotaje	M16x1,5 VOSS																																																																																	
21	Delivery / Salida	M22x1,5 VOSS																																																																																	
22	Delivery / Salida	M22x1,5 VOSS																																																																																	
3	Exhaust / Escape	M22x1,5																																																																																	
D																																																																																			
Purpose / Propósito: Application of service brake system through the pedal actuation by the driver. / Aplicación del freno de servicio mediante la actuación del pedal por parte del conductor.																																																																																			
Installation requirements / Requisitos para la instalación: The design of the foot brake valve, acting on seat, must guarantee the maximum way of the push rod that is necessary to control the valve even in case of failure in the circuit I. Mounting is accomplished with two mounting bolts M8. / El diseño de la válvula de freno de pie, accionándolo desde el asiento, debe garantizar el máximo recorrido de la varilla de empuje que resulta necesario para el accionamiento de la válvula, incluso en caso de que falle el circuito I. El montaje se efectúa con dos pernos de montaje M8.																																																																																			
E																																																																																			
<table><tr><td rowspan="5">Modification</td><td>4</td><td></td><td></td><td></td><td></td><td>Drawn</td><td colspan="2" rowspan="5"></td></tr><tr><td>3</td><td></td><td></td><td></td><td></td><td>12/08/15 A.U.</td></tr><tr><td>2</td><td></td><td></td><td></td><td></td><td>Checked</td></tr><tr><td>1</td><td></td><td></td><td></td><td></td><td>12/08/15 A.L.</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>F</td><td>nº</td><td>Modified</td><td>Date</td><td>Reason</td><td>General Tolerance</td><td>Assembly</td><td colspan="2">-</td></tr><tr><td colspan="5">Comments</td><td>-</td><td>Part name</td><td colspan="2">Foot brake valve</td></tr><tr><td colspan="5"></td><td>Material</td><td>ID. Reference</td><td colspan="2">2312605</td></tr><tr><td colspan="5"></td><td>-</td><td>Scale: -</td><td rowspan="2"></td><td rowspan="2">Sheet 1/2</td></tr><tr><td colspan="5"></td><td>-</td><td>Review: 0</td></tr></table>								Modification	4					Drawn			3					12/08/15 A.U.	2					Checked	1					12/08/15 A.L.							F	nº	Modified	Date	Reason	General Tolerance	Assembly	-		Comments					-	Part name	Foot brake valve							Material	ID. Reference	2312605							-	Scale: -		Sheet 1/2						-	Review: 0
Modification	4					Drawn																																																																													
	3					12/08/15 A.U.																																																																													
	2					Checked																																																																													
	1					12/08/15 A.L.																																																																													
F	nº	Modified	Date	Reason	General Tolerance	Assembly	-																																																																												
Comments					-	Part name	Foot brake valve																																																																												
					Material	ID. Reference	2312605																																																																												
					-	Scale: -		Sheet 1/2																																																																											
					-	Review: 0																																																																													
PG/18/02 rev.1 1		2		3		4																																																																													



F	Modification	4				Drawn			F
		3				12/08/15 A.U.			
		2				Checked			
		1				12/08/15 A.L.			
		nº	Modified	Date	Reason	General Tolerance			
	Comments				ISO 2768 c-K	Part name	Foot brake valve		
					Material	ID. Reference	2312605		
-					Scale: 1/2		Sheet 2/2		
					Review: 0				
PG/18/02 rev.1 1			2		3		4		