

1		2		3		4	
A							
Technical sheet / Datos técnicos:							
Part number adaptable to / Referencia adaptable a						9735000310	
Supply pressure / Presión de alimetación						max 12 bar	
Permissible medium / Medio de funcionamiento						Air / Aire	
Operating temperature range / Rango de temperatura						-40 °C to / a +80 °C	
Weight / Peso						300 gr	
B							
C							
D							
Port / Conexión		Function / Función				Thread / Rosca	
1		Supply / Alimentación				M22x1.5	
21-23		Delivery / Salida				2x M22x1.5	
22		Delivery / Salida				M16x1.5	
3		Exhaust / Escape				-	
E							
Purpose / Propósito: To quickly eject the air from any reservoir and to achieve an increase in its operating speed. / Desalojar rápidamente el aire de los actuadores de freno para conseguir una rapidez de respuesta de frenado adecuada. Installation requirements / Requisitos para la instalación: To install the valve with the exhaust port facing downwards. The valve must be installed using two screws M8. / Instalar la válvula con el escape orientado hacia abajo. La válvula debe ser instalada utilizando dos tornillos M8.							
F							
Modification	4					Drawn	
	3					21/08/13 A.U.	
	2					Checked	
	1					21/08/13 A.L.	
	nº	Modified	Date	Reason	General Tolerance	Assembly	-
Comments					-	Part name	Quick release valve
					Material	ID. Reference	2221212
					-	Scale: -	
					-	Review: 0	
PG/18/02 rev.1 1		2		3		4	

